

## Pressure reducer

Equipped with pressure gauge with sensor



Two-stage pressure reducer with fixed setting suitable for direct connection to the tank. The pressure gauge with resistive sensor, allows to send the electrical signal to a dedicated switch.

### Specific Characteristics

Compact and reliable  
 Inlet connection standard UNI  
 Safety valve  
 Outlet connection  $\varnothing$ 7mm hose  
 Sintered bronze filter integrated in the device

### Technical data

|                     |                                     |
|---------------------|-------------------------------------|
| Dimensions          | 130x90x150 mm                       |
| Weight              | 1,45 kg                             |
| Max inlet pressure  | 230 bar                             |
| Output pressure     | Setted to 4 bar                     |
| Flow                | 150 l/min                           |
| Filter              | 60 $\mu$                            |
| Materials           | Chromed brass, Steel, Bronze, Vyton |
| Sensor cable length | 2,5 m                               |

Class IIb Med.Device according to Dir. 93/42/CEE

PRESSURE REDUC. 3,5BAR-150  
 L/MIN W/MANOM W/SENSOR

**PR00326B**

**CND Classification**



Z120309

Distributed by Spencer Italia S.r.l

Rev.1 (15/01/2018)

UNCHECKED COPY – further revisions will be available on <http://support.spencer.it>

Spencer Italia S.r.l. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222

[www.spencer.it](http://www.spencer.it)