JET WIRE Portable suction device





The device is to be used to remove fluids from the airway or respiratory support system and infectious materials from wounds. The device creates a negative pressure (vacuum) that draws fluids through disposable tubing that is connected to a collection canister. The fluids are trapped in the collection canister for proper disposal. It is for use on the order of a physician only.

Specific Characteristics	
Light and compact	
Easy view of the setted vacuum thanks to the led	
indicators	
Capacious and reusable canister	
Classification ISO High Vacuum/ High Flow	
Standard Equipment	
Battery	
Reusable canister	
Sterile patient tube	
Antibacterial filter	
12V cigarette lighter cable	
Spare parts	
RISCOO5E – SPARE FILTER	
SC70085A - CANISTER 1L W/COVER	
SC73016E – STERILE SUCTION TUBE	

Compliant with

ISO 10079-1 RTCA/DO-160E DO-160E – Section 21 Category M (for battery operation only; commercial aircraft, airborne equipment)

Technical data	
Dimensions	185x205x220 mm
Weight	1,98 kg
Vacuum range	From 50 to 550 mmHg
Flow (free flow)	27 l/min
Noise level	70 dB
Electrical connection	100-240 VAC 47-63 Hz 0,75
requirements	A max ; 12VDC 33W max
IP protection	IP 12
Battery	12V DC Ni-MH
Mode of Operation	30 min ON, 30 min OFF
Battery recharging time	5 h
Canister capacity	1000 ml
Patient tube	1,8 m
Operating temp.	From 0°C to +40°C
Storage temp.	From -40°C to +70°C
Humidity	From 0 to 95%

Humidity
Class IIa Med.Device according to Dir. 93/42/CEE
JET WIRE HOMECARE
SC75400C

Distributed by Spencer Italia S.r.l.

Rev.2 (15/01/2018)

UNCHECKED COPY – further revisions will be available on <u>http://support.spencer.it</u> Spencer Italia S.r.I. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222

www.spencer.it

© Copyright - This document is property of SPENCER ITALIA S.r.I and can't be reproduced, used and disclosed without the written approval of SPENCER ITALIA S.r.I.