

## AMBUJET P 1000 R 10G

Portable suction device with 10G wall fixing with auto recharge





Space-saving suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container. The base performs the dual function of charging station and fixing in accordance to EN 1789 standard.

	Specific Characteristics
	low weight and size
	Easy view of the setted vacuum thanks to the led indicators
	Classification ISO High Vacuum/ High Flow
	Suction device protected from bumps and falls thanks to the protective shell
	Mechanism of engagement and release from the base extremely rapid
	Recharging of the battery is done simply by placing the device on the mounting system

Standard Equipment	
Fixing with integrated charging system	
Battery	
Reusable canister	
Disposable patient tube 1,8 m	
Shoulder strap for easy transport	

Optional acce	essories/Consumables
SC75012E	Lateral bags for Jet
SC75014D	SUPPLY CABLE FOR CIG.LIGHTER 12VCC
SC73017E	220V Power supply
SC73013E	Antibacterial filter
SC73016E	Sterile suction catheter 1,8m

Compliant with		
ISO 10079-1		
EN 1789		

Technical data	
Jet Dimensions	200x225x285 mm
Jet Dimensions w/fastener	200x250x320 mm
Suction device weight	2,4 ± 0,1 kg
Fixing weight	0,8 kg
Vacuum Range	From 50 to 550 mmHg
Flow (free flow)	32 l/min
Noise level	70 db
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75A max; 12VDC 33W max
IP Grade	IP12
Battery	12V DC Ni-MH
Operating time	30 min. ON, 30 min. OFF
Battery recharging time	5 h
Container capacity	1000 ml
Patient tube lenght	1,8 m
Operating temp.	From 0°C to +45°C
Storage temp.	From – 40°C to +70°C
Umidity	From 0 to 95%

Class IIa Med.Device accordin	ng to Dir. 93/42/CEE
AMBUJET P 1000 R 10G	
SC75650D	C C <sub>0434</sub>
Registration number	81603