

AMBUJET 1000 B 20G

Portable suction device
with 20G wall fixing



Space-saving suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container. The base is fastener in accordance to EN 1789 standard.

Specific Characteristics

- Low weight and size
- Easy visualization of the selected vacuum thanks to the LED lights
- Mechanism of engagement and release from the base extremely rapid
- Classification ISO High Vacuum/ High Flow
- Wide base to increase stability
- The shell provides protection to the suction unit
- Simple and intuitive controls

Standard Equipment

- 20G fastener
- Battery
- Serres canister with disposable bag
- Disposable patient tube 1,8 m
- Shoulder strap for easy transport

Optional accessories/Consumables

SC75012E	Lateral bags for Jet
SC73017E	220V Power supply
RISC006B	Antibacterial filter
SC73016E	Sterile suction catheter 1,8m
SC75018E	36 disposable bags for canister
SC75022	Power supply cable male connector BS

Compliant with

ISO 10079-1
EN 1789

Technical data

Jet Dimensions	200x225x285 ± 5 mm
Jet Dimensions w/fixing	200x250x320 ± 5 mm
Weight with fastener	3,1 ± 0,1 kg
Vacuum Range	Da 50 a 550 mmHg
Flow (free flow)	32 l/min
Noise level	70 db
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75 A max; 12VDC 33W max
IP Grade	IP12
Battery	12V DC Ni-MH
Battery operating time	Max 45-60min at free flow
Battery recharging time	5 h
Operation mode	30 min. ON, 30 min. OFF
Container capacity	1000 ml
Patient tube length	1,8 m
Operating temp.	From 0°C to +45°C
Storage temp.	From - 40°C to +70°C
Humidity	From 0 to 95%

Ass. Med.Device according to Dir. 93/42/CEE

AMBUJET 1000 B 20G

SC75710B



Rev.1 (15/01/2018)

UNCHECKED COPY – further revisions will be available on <http://support.spencer.it>
Spencer Italia S.r.l. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222

www.spencer.it