

## **AMBUJET 800 D 10G**

Portable suction device with 10G wall fastener





Space-saving suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container. The base performs as a fastener in accordance to EN 1789 standard.

	Specific Characteristics
	Low weight and size
	Easy view of the vacuum set thanks to the led indicators
	Classification ISO High Vacuum/ High Flow
	Suction device protected from bumps and falls thanks to the protective shell
	Mechanism of engagement and release from the base extremely rapid
	Direct connection between canister and vacuum pump

Standard Equipment
10g fastener with quick unlocking system
Battery
Disposable canister
Disposable patient tube 1,8 m
Shoulder strap for easy transport

Optional accessories/Consumables			
SC75012E	Lateral bags for Jet		
SC75014D	O14D Supply cable for cig.lighter 12vcc		
SC73017E	220V Power supply		
RISC005E	Antibacterial filter		
SC73016E	Sterile suction catheter 1,8m		
SC73039E	800 ml disposable canisters (10pcs set)		

Compliant with		
	ISO 10079-1	
	EN 1789	

Technical data		
Jet Dimensions	200x225x285 mm	
Jet Dimensions w/fastener	200x250x320 mm	
Suction device weight	2,4 ± 0,1 kg	
Fastener weight	0,8 ± 0,1 kg	
Vacuum Range	From 50 to 550 mmHg	
Flow (free flow)	32 l/min	
Noise level	70 dB	
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75A max; 12VDC 33W max	
IP Grade	IP12	
Battery	12V DC Ni-MH	
Operating time	30 min. ON, 30 min. OFF	
Battery recharging time	5 h	
Container capacity	800 ml	
Patient tube lenght	1,8 m	
Operating temp.	From 0°C to +45°C	
Storage temp.	From – 40°C to +70°C	
Umidity	From 0 to 95%	

Med.Device CE marked acco	ording to Dir. 93/42/CEE
AMBUJET 800 D 10G	
SC75750C	C C <sub>0044</sub>
Registration number	81604