

AMBUJET 1000 B 10G

Portable suction device with 10G wall fixing





Space-saving suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container. The base is fastener in accordance to EN 1789 standard.

Specific Characteristics
Low weight and size
Easy visualization of the selected vaccum thanks to the LED lights
Mechanism of engagement and release from the base
extremely rapid
Classification ISO High Vacuum/ High Flow
Wide base to increase stability
The shell provides protection to the suction unit
Simple and intuitive controls

Standard Equipment
10G fastener
Battery
Serres canister with disposable bag
Disposable patient tube 1,8 m
Shoulder strap for easy transport

Optional acco	Optional accessories/Consumables				
SC75012E	Lateral bags for Jet				
SC73017E	220V Power supply				
RISC006B	Antibacterial filter				
SC73016E	Sterile suction catheter 1,8m				
SC75018E	36 disposable bags for canister				
SC75022	Power supply cable male connector BS				

Compliant with
ISO 10079-1
EN 1789

Technical data	ical data			
Jet Dimensions	200x225x285 ± 5 mm			
Jet Dimensions w/fixing	200x250x320 ± 5 mm			
Weight with fastener	$3,1 \pm 0,1 \text{ kg}$			
Vacuum Range	From 50 to 550 mmHg			
Flow (free flow)	32 I/min			
Noise level	70 db			
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75 A max; 12VDC 33W max			
IP Grade	IP12			
Battery	12V DC Ni-MH			
Battery operating time	Max 45-60min at free flow			
Battery recharging time	5 h			
Operation mode	30 min. ON, 30 min. OFF			
Container capacity	1000 ml			
Patient tube lenght	1,8 m			
Operating temp.	From 0°C to +45°C			
Storage temp.	From – 40°C to +70°C			
Humidity	From 0 to 95%			

Ass. Med.Device according to Dir. 93/4	12/CEE	
AMBUJET 1000 B 10G		
SC75760B		
		0434

Rev.1 (15/01/2018)