

## **AMBUJET 1000 R 20G**

Portable suction device with 20G wall fastener





Space-saving suction device to be used to remove fluids from the airway or respiratory support system. The device creates a negative pressure that draws fluids through disposable tubing that is connected to the collection container. The base performs as a fastener in accordance to EN 1789 standard.

	Specific Characteristics
	low weight and size
	Easy view of the vacuum set thanks to the led indicators
	Classification ISO High Vacuum/ High Flow
	Suction device protected from bumps and falls thanks to the protective shell
	Mechanism of engagement and release from the base extremely rapid
	Direct connection between canister and vacuum pump

Standard Equipment
20g fastener with quick unlocking system
Battery
Reusable canister
Disposable patient tube 1,8 m
Shoulder strap for easy transport

Optional accessories/Consumables		
SC75012E	Lateral bags for Jet	
SC75014D	SUPPLY CABLE FOR CIG.LIGHTER 12VCC	
SC73017E	220V Power supply	
SC73013E	Antibacterial filter	
SC73016E	Sterile suction catheter 1,8m	

Compliant with	
ISO 10079-1	
EN 1789	

Technical data	
Jet Dimensions	200x225x285 mm
Jet Dimensions w/fastener	200x250x320 mm
Suction device weight	2,4 ± 0,1 kg
Fixing weight	0,8 ± 0,1 kg
Vacuum Range	From 50 to 550 mmHg
Flow (free flow)	32 l/min
Noise level	70 db
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75A max; 12VDC 33W max
IP Grade	IP12
Battery	12V DC Ni-MH
Operating time	30 min. ON, 30 min. OFF
Battery recharging time	5 h
Container capacity	1000 ml
Patient tube lenght	1,8 m
Operating temp.	From 0°C to +45°C
Storage temp.	From – 40°C to +70°C
Umidity	From 0 to 95%

Med.Device CE marcked acc	ording to Dir. 93/42/CEE
AMBUJET 1000 R 20G	
SC75800C	C C <sub>0044</sub>
Registration number	79763