

JET COMPACT HOMECARE

Portable suction device



The device is to be used to remove fluids from the airway or respiratory support system and infectious materials from wounds. The device creates a negative pressure that draws fluids through disposable tubing that is connected to a collection canister. The fluids are trapped in the collection canister for proper disposal. It is for use on the order of a physician only.

Specific Characteristics

- Light and compact
- Easy view of the setted vacuum thanks to the led indicators
- Classification ISO High Vacuum/ High Flow

Standard Equipment

- 220V/12V power supply with cable and .Schucko socket
- Battery
- Disposable canister with filter
- Disposable patient tube

Spare parts

- SC75001E- DISP. JAR 300ml FOR JET W/PATIENT TUBE

Compliant with

- ISO 10079-1
- RTCA/DO-160E DO-160E – Section 21 Category M (for battery operation only; commercial aircraft, airborne equipment)

Technical data

Dimensions	245x70x185 mm
Weight	1,54 kg
Power supply weight	520 g
Vacuum Range	From 50 to 550 mmHg
Flow (free flow)	27 l/min
Noise level	70 dB
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75 A max ; 12VDC 33W max
IP protection	IP 12
Battery	12V DC Ni-MH
Mode of operation	30 min ON, 30 min OFF
Battery recharging time	5 h
Container capacity	300 ml
Patient tube length	1 m
Operating temp.	From 0°C to +45°C
Storage temp.	From -40°C to +70°C
Humidity	From 0 to 95%

Class IIa Med.Device according to Dir. 93/42/CEE

JET COMPACT HOMECARE

SC76100D



7310PD-S Model number of suction device main body

Distributed by Spencer Italia S.r.l.

Rev.1 (15/01/2018)

UNCHECKED COPY – further revisions will be available on <http://support.spencer.it>
Spencer Italia S.r.l. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222
www.spencer.it