

JET WIRE HOMECARE

Portable suction device



The device is to be used to remove fluids from the airway or respiratory support system and infectious materials from wounds. The device creates a negative pressure (vacuum) that draws fluids through disposable tubing that is connected to a collection canister. The fluids are trapped in the collection canister for proper disposal. It is for use on the order of a physician only.

Specific Characteristics

Light and compact
 Easy view of the setted vacuum thanks to the led indicators
 Capacious and reusable canister
 Classification ISO High Vacuum/ High Flow

Standard Equipment

220V/12V power supply with cable and Schucko socket
 Battery
 Reusable canister
 Sterile patient tube
 Antibacterial filter

Spare parts

SC70077E - FILTER, SILICON TUBE AND CONNECTOR
 SC70085A - CANISTER 1L W/COVER
 SC73016E – STERILE SUCTION TUBE

Compliant with

ISO 10079-1
 RTCA/DO-160E DO-160E – Section 21 Category M
 (for battery operation only; commercial aircraft,
 airborne equipment)

Technical data

Dimensions	185x205x220 mm
Weight	1,98 kg
Powver supply weight	520 g
Vacuum range	From 50 to 550 mmHg
Flow (free flow)	27 l/min
Noise level	70 dB
Electrical connection requirements	100-240 VAC 47-63 Hz 0,75 A max ; 12VDC 33W max
IP protection	IP 12
Battery	12V DC Ni-MH
Mode of Operation	30 min ON, 30 min OFF
Battery recharging time	5 h
Canister capacity	1000 ml
Patient tube	1,8 m
Operating temp.	From 0°C to +40°C
Storage temp.	From -40°C to +70°C
Humidity	From 0 to 95%

Class IIa Med.Device according to Dir. 93/42/CEE

JET WIRE HOMECARE

SC76400C



7310PD-S Model number of suction device main body

Distributed by Spencer Italia S.r.l.

Rev.1 (15/01/2018)

UNCHECKED COPY – further revisions will be available on <http://support.spencer.it>
 Spencer Italia S.r.l. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222
www.spencer.it