

DAVIS

Traction/immobilization system



Davis traction systems are devices that limit tissue damage caused by possible bone rubbing by spacing the two halves of a fracture.

Specific features

- Sturdy and lightweight structure
- 4 padded supports offer greater comfort and a better weight distribution
- Elastic immobilization bands
- Padded and adjustable ankle band
- Soft ischial padding increase leg stability and patient comfort
- Transport bag with pocket and strap closure allows easy storage of the device and accessories

Technical data

Minimum length ⁽¹⁾	890 ± 10 mm
Maximum length ⁽¹⁾	1350 ± 10 mm
Width	210 mm
Base width	230 mm
Width of leg support area	165 mm
Traction belt length	From 0 to 500 mm
Inclination	10° (variable depending on the extension)
Materials	Steel, Al, Nylon
Weight	1.78 ± 0.1 kg
Bag dimensions	990 x 330 mm
Bag weight	520 g

⁽¹⁾ The limb must be approximately 15 cm shorter than the indicated measurements

Sizes subject to ± 10 mm tolerances

Standard equipment

Transport bag

Class I MD compliant with UE Reg. 2017/745

DAVIS ADULT TRACTION SYSTEM



SR01010A

CND Classification V9099

Registration number 195373

Nato stock N° 6515-15-149-2408

Rev.0 (10/09/2021)

UNCHECKED COPY – further revisions will be available on <http://support.spencer.it>
 Spencer Italia S.r.l. Sala Baganza (PR) Italia Tel. +39.0521.541111 Fax +39.0521.541222
www.spencer.it